## HHS Specifications

					<b>Burner Fuel</b>			
Model No.	PSI	GPM	HP/Motor	Plug Type	Tank Cap.	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHS-1002-1E1G#	1000	2.0	1.5/120V, 1Ø, 16.2A	NEMA 5-20P	10.0 gallon	57in.x30in.x41.5in.	606 lbs.	486 lbs.
HHS-1003-1E1G#	1000	2.8	2.0/120V, 1Ø, 20.0A	NEMA 5-20P	10.0 gallon	57in.x30in.x41.5in.	610 lbs.	490 lbs.
HHS-1502-1E1G#	1500	1.8	2.0/115V, 1Ø, 19.9A	NEMA 5-20P	10.0 gallon	57in.x30in.x41.5in.	610 lbs.	490 lbs.
					Burner Fuel			
Model No.	PSI	GPM	HP/Motor	Plug Type	Tank Cap.	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHS-2004-1E2G#	2000	4.2	6.0/230V, 1Ø, 28.0A	NEMA 6-30P	10.0 gallon	57in.x30in.x41.5in.	670 lbs.	550 lbs.
HHS-2004-1E3G#	2000	4.2	6.0/230V, 3Ø, 28.0A	NEMA L15-20P	10.0 gallon	57in.x30in.x41.5in.	670 lbs.	550 lbs.
HHS-2004-1E4G#	2000	4.2	6.0/460V, 3Ø, 12.0A	NEMA L16-20P	10.0 gallon	57in.x30in.x41.5in.	670 lbs.	550 lbs.
HHS-2004-1E8G#	2000	4.2	6.0/208V, 1Ø, 30.7A	NEMA 6-50P	10.0 gallon	57in.x30in.x41.5in.	670 lbs.	550 lbs.
HHS-2004-1E9G#	2000	4.2	6.0/208V, 3Ø, 29.9A	NEMA L15-30P	10.0 gallon	57in.x30in.x41.5in.	670 lbs.	550 lbs.
					Burner Fuel			
Model No.	PSI	GPM	HP/Motor	Plug Type	Tank Cap.	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHS-3004-1E2G#	3000	3.9	8.0/230V, 1Ø, 39.5A	NEMA 6-50P	10.0 gallon	57in.x30in.x41.5in.	700 lbs.	580 lbs.
HHS-3004-1E3G#	3000	3.9	8.0/230V, 3Ø, 27.5A	NEMA L15-30P	10.0 gallon	57in.x30in.x41.5in.	700 lbs.	580 lbs.
HHS-3004-1E4G#	3000	3.9	8.0/460V, 3Ø, 14.0A	NEMA L16-20P	10.0 gallon	57in.x30in.x41.5in.	700 lbs.	580 lbs.
HHS-3004-1E5G#	3000	3.9	8.0/575V, 3Ø, 12.0A	NEMA L17-30P	10.0 gallon	57in.x30in.x41.5in.	700 lbs.	580 lbs.
HHS-3004-1E8G#	3000	3.9	8.0/208V, 1Ø, 43.0A	NEMA 6-50P	10.0 gallon	57in.x30in.x41.5in.	700 lbs.	580 lbs.
HHS-3004-1E9G#	3000	3.9	8.0/208V, 3Ø, 25.5A	NEMA L15-30P	10.0 gallon	57in.x30in.x41.5in.	700 lbs.	580 lbs.
					Burner Fuel			
Model No.	PSI	GPM	HP/Motor	Plug Type	Tank Cap.	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHS-3005-1E2G#	3000	4.8	10.0/230V, 1Ø, 46.5A	NEMA 6-50P	10.0 gallon	57in.x30in.x41.5in.	704 lbs.	584 lbs.
HHS-3005-1E3G#	3000	4.8	10.0/230V, 3Ø, 27.5A	NEMA L15-30P	10.0 gallon	57in.x30in.x41.5in.	704 lbs.	584 lbs.
HHS-3005-1E4G#	3000	4.8	10.0/460V, 3Ø, 16.5A	NEMA L16-20P	10.0 gallon	57in.x30in.x41.5in.	704 lbs.	584 lbs.
HHS-3005-1E5G#	3000	4.8	10.0/575V, 3Ø, 14.0A	NEMA L17-30P	10.0 gallon	57in.x30in.x41.5in.	704 lbs.	584 lbs.
HHS-3005-1E8G#	3000	4.8	10.0/208V, 1Ø, 50.7A	NEMA 6-50P	10.0 gallon	57in.x30in.x41.5in.	704 lbs.	584 lbs.
HHS-3005-1E9G#	3000	4.8	10.0/208V, 30, 31.5A	NEMA L15-50P	10.0 gallon	57in.x30in.x41.5in.	704 lbs.	584 lbs.
			· ·		-			
HHS-303-1E1A^	300	2.5	1.5/120V, 1Ø, 12.5A	GFCI 15 Amp	10.0 gallon	57in.x30in.x41.5in.	480 lbs.	460 lbs.
	# Not	te AR Pun	nns are available on all models	s. ^Steamer unit				

# Note AR Pumps are available on all models. ^Steamer unit

Options: 50-0170 850-0324 HX-0161

HX-0164 HX-0165, HX-0167

TX-1304-W

**Stack adapter -** Allows 8-inch flue pipe to be installed to boiler exhaust port Gasket (for 50-0170) - Seals between 50-0170 stack adapter and boiler housing

**Hour meter -** Displays number of hours unit has been in operation

HX-0162 Stainless-steel bottom wrap - Coverts powder coated paint bottom wrap to stainless-steel

HX-0163

13-inch mag tires - Upgrade to mag tires from white rims
Time delay shutdown - Timer will shut unit off automatically when trigger gun is released and timer reaches setting

Option ready kit - This option is required if adding time delay shut down or auto start/stop Auto start/stop - When trigger gun is released timer will turn unit off, when trigger gun is pulled unit will restart

Skid feet - Stationary applications

HX-0171 HX-0172 - HX-0176 & HX-0195 250° Steam - Increases outlet temperature to 250°F HX-0196 **Skid frame/roll cage design -** Stationary applications

NEMA L17-30P, 30-amp plug

Puncture-proof tires - Tires are flat-free, maintenance-free, 13-inch, white hub, four tires

Model #	50-0170	850-0324	HX-0161	HX-0162	HX-0163	HX-0164	HX-0165	HX-0166	HX-0167	HX-0171	HX-0172	HX-0173	HX-0174
HHS-1002	•	•	•	•	•	•	•	•		•	•		
HHS-1003	•	•	•	•	•	•		•	•	•			•
HHS-1502	•	•	•	•	•	•		•	•	•			
HHS-2004	•	•	•	•	•	•		•		•		•	
HHS-3004	•	•	•	•	•	•		•		•	•		
HHS-3005	•	•	•	•	•	•		•		•			
HHS-303	•	•	•	•	•	•		•		•			

Model #	HX-0176	HX-0195	HX-0196	TX-1304-W
HHS-1002			•	•
HHS-1003			•	•
HHS-1502		•	•	•
HHS-2004			•	•
HHS-3004			•	•
HHS-3005	•		•	•
HHS-303			•	•

NEMA L16-20P, 20-amp plug



NEMA 6-50P, 50-amp plug





NEMA L15-20P, 20-amp plug NEMA L15-30P, 30-amp plug

Distributed by:



## Hot Water Pressure Washers **HHS Series**





## **HHS Series**

The HHS Series offers portability and reliability suitable for the most rugged applications.

ELECTRIC POWERED - OIL HEATED - BELT DRIVE

PORTABLE



Belt drive triplex General or AR plunger pump has the best warranty in the industry



Racor fuel/water separator ensures clean fuel supply to the burner



Optional stack adapter allows 8-inch flue pipe to be installed to vent machine exhaust



Locking rear wheel brake prevents unit from rolling





- ✓ Easy pump oil drain
- ✓ Thermal relief valve
- ✓ Pressure switch and high limit switch safety controls
- √ 300°F/149°C operating temperature (HHS-303 only)
- ✓ Wand holder
- ✓ Insulated trigger gun
- ✓ Adjustable pressure-insulated dual lance/wand (except on HHS-303)
- ✓ Single lance with dual insulated grips; steam nozzle (HHS-303)
- ✓ 50-foot x 3/8-inch high pressure hose with quick connects (50-foot steam hose on HHS-303)



HHS-2004-1E4G shown with skid frame (HX-0196) option

















